

# GasAlert EXTREME

## Single-Gas Detector

H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, NH<sub>3</sub>, PH<sub>3</sub>, Cl<sub>2</sub>, ClO<sub>2</sub>, NO, NO<sub>2</sub>, HCN, ETO, O<sub>3</sub>





### Long-term solution

Compact and affordable, the GasAlert Extreme reliably monitors for any single gas hazard within its wide range of available toxic gas models. With easy on/off operation, this single gas detector offers extended longevity with a field-replaceable battery and sensor. A wide range of tamperproof user options and multi-language display make the GasAlert Extreme an ideal solution for a variety of applications; plus, datalogging is standard on all units. Calibration is a simple automatic procedure and is compatible with BW's MicroDock II automatic test and calibration system.

### Standard Package Contents

- Detector complete with specified sensor, stainless steel alligator clip and concussion-proof housing
- Calibration/test cap and hose
- Manual

### General Specifications

<b>Size</b>	1.1 x 2.0 x 3.75 in. / 2.8 x 5.0 x 9.5 cm
<b>Weight</b>	2.9 oz. / 82 g
<b>Typical battery life</b>	1.5 year battery life (typical) with replaceable 3V battery
<b>Certifications and Approvals</b>	 Class I, Div. 1, Gr. A, B, C, D Class II, Div. 1, Gr. E, F, G  American Bureau of Shipping <b>ATEX:</b> II 1 G Ex ia IIC T4 Ga <b>CE:</b> European Conformity <b>IECEX:</b> Ex ia IIC T4 Ga <b>IP Rating:</b> IP 66/67
<b>Warranty</b>	Full two year warranty including sensors (One year Cl <sub>2</sub> , NH <sub>3</sub> , O <sub>3</sub> , ETO and ClO <sub>2</sub> sensors)